



Features

Excellent cleaning performance Easy operation and maintenance Ergonomic and effort saving features



Enhanced gun and stainless steel provide a long service life

Rubber wheels make transportation easy

LEO engines provide dependable power and a long service; easy to start and simple to operate

Front carry handle makes carrying easy

Efficient boosting pump provides excellent discharge pressure

Specifications	LPW2000	LPW2500
Engine type	Air-cooled,4-stroke,Single cylinder	Air-cooled, 4-stroke, Single cylinder
Engine displacement	139 ℃	173 cc
Speed	2900 rpm	2900 rpm
Power	5.5 HP	6.5 HP
Max pressure	2000 PSI	2500 PSI
Max flow rate	7.2 L/min	7.5 L/min
Pump outlet connection	M22 screw thread	M22 screw thread
Hose diameter	6.4 mm	6.4 mm
Hose length	8 m	8 m
Nozzle	4 tips:0,15,25,40	4 tips:0,15,25,40
Wheel size	190 mm/7.5"	190 mm/7.5"
Gun and lance	Trigger gun and 20" stainless steel lance	Trigger gun and 20" stainless steel lance
Net weight	24.6 kgs	24.15 kgs
Package size	540x487x520 mm	540x487x520 mm
Loading Q'ty	192/384/480pcs	192/384/480pcs