



Features

- Engineering plastic pump body
- Float switch ensures automatic cut-in and cut-out
- Built-in thermal protector

Application

- Can be used for transfer clean water or other liquids similar to water in physical and chemical properties
- Suitable to be immersed in water for lifting water from well or the pool, and draining water from the basement

Model	AKS-251PH	AKS-401PH
Rated Power	250 W	400 W
Max. Head	6 m	6 m
Max. Flow	6 m³/h	9 m³/h
Max. Depth of immersion	7 m	7 m
Max. Dia of Particle	5 mm	5 mm
Outlet	1 1/4"	1 1/4"
Power Cable Type	H05RN-F	H05RN-F
Length of Power Cable	10 m	10 m
Protection Class	IPX8	IPX8
Max. liquid Temperature	35°C	35°C
Qty in carton box	4 pcs	4 pcs
Package Dimension	440x350x300 mm	440x350x300 mm
Package Gross Weight	15.29 kg	16.212 kg
Qty/20'GP	2700	2700
Automatic function	Float Switch	Float Switch



Features

- Engineering plastic pump body
- Float switch ensures automatic cut-in and cut-out
- Built-in thermal protector

Application

- Can be used for transfer clean water or slightly dirty water or other liquids similar to water in physical and chemical properties
- Suitable to be immersed in water for lifting water from well or the pool, and draining water from the basement

Model	AKS-251PWH	AKS-401PWH	AKS-551PWH	AKS-751PWH
Rated Power	250 W	400 W	550 W	750 W
Max. Head	5 m	5 m	7 m	8 m
Max. Flow	6 m³/h	9 m³/h	12 m³/h	14 m³/h
Max. Depth of immersion	7 m	7 m	7 m	7 m
Max. Dia of Particle	25 mm	25 mm	35 mm	35 mm
Outlet	1 1/4"	1 1/4"	1 1/2"	1 1/2"
Power Cable Type	H05RN-F	H05RN-F	H05RN-F	H05RN-F
Length of Power Cable	10 m	10 m	10 m	10 m
Protection Class	IPX8	IPX8	IPX8	IPX8
Max. liquid Temperature	35°C	35°C	35°C	35°C
Qty in carton box	4 pcs	4 pcs	4 pcs	4 pcs
Package Dimension	440x350x330 mm	440x350x330 mm	420x350x370 mm	420x350x370 mm
Package Gross Weight	17.6 kg	18.8 kg	21.2 kg	22.4 kg
Qty/20'GP	2700	2700	2700	2700
Automatic function	Float Switch	Float Switch	Float Switch	Float Switch